



Innovativeness Design

A4 paper size, streamline design



Intelligent Control

Wireless communication (WiFi/Bluetooth)
OCPP communication protocol with the
backend
Smart charge or scheduled charge by App



Flexible Option

Type 1 or Type 2 charging cable App operation or plug and play Wall-mounted or floor-stand installation



Secure and Safe

6mA DC residual current protection Anti-welding protection IP65 rated

Power: 7.3kW

Output Current: Max.32A

Output Voltage: 230V AC

- Type 2 cable charging connector
- Compliant with OCPP 1.6 (JSON)/2.0
- App operation or RFID authentication or plug, play & 4G
- Protection Grade: IP54
- −25 ~ 50 °C wide Operating Temperature



For more about the FoxESS EV charger Please visit:

WWW.FOX-ESS.COM









7.3KW EV CHARGER





MODEL	A7300P1-E	A7300S1-E
ТҮРЕ	CHARGING PLUG	CHARGING SOCKET
INPUT		
Power Supply	1P+N+PE	
Rated Voltage	230Vac, ±20%	
Rated Current	32A	
Frequency	50/60Hz	
OUTPUT		
Output Voltage	230Vac, ±20%	
Maximum Current	32A	
Rated Power	7.3kW	
USER INTERFACE		
Charge Connector	Type 2 cable	Type 2 socket
RFID Reader	Mifare ISO/IEC	C 14443 A
Start Mode	Plug&Play/RFID card/App	
Emergency Stop	Yes	
COMMUNICATION		
WiFi, Bluetooth	Yes	
4G, Ethernet	Optional (coming soon)	
ОСРР	OCPP 1.6 JSON, OCPP 2.0 optional (coming soon)	
ENVIRONMENT		
Installation	Wall-mount/Pedestal-mount	
Operating Temperature	-25°C ~ 50°C	
Humidity	5% ~ 95% No condensation	
Altitude	≤2000m	
PACKAGE		
Product Dimension	300*210*130 mm	
External Package	Carton	
SAFETY		
Ingress Protection	IP54	
Impact Protection	IK08	
RCD	6mA DC	
Electrical Protection	Over current protection, Residual current protection, Ground protection, Surge protection,	
	Over/Under voltage protection, Over/Under frequency protection, Over/Under temperature protection	
EMC	Class B	
Certification	CE	
Certification Standard	EN/IEC 61851-1: 2017, EN/IEC 61851-21-2: 2018	
PRODUCT CONFIGURATION	ENVILE 01031 1. 2017, ENVILE 01031-21-2. 2010	
Bluetooth + RFID Reader + Wifi	Yes	
4G + RFID Reader	Coming soon	
TO - MID Meddel		