



M1

Micro Inverter series

REFINED – POWERFUL – FLEXIBLE



**High Performance**

Low startup voltage,  
 Wide voltage range,  
 More efficient.



**Easy Installation**

Flexible configuration, plug and  
 play set-up.



**IP67 Rated**

Engineered to last with  
 maximum flexibility. Suitable  
 for outdoor installation.



**Remote Monitoring**

Monitor your system  
 remotely via smartphone  
 app or web portal.

ANYTIME, ANYWHERE  
**REMOTE  
 MONITORING  
 PLATFORM**

Monitor system performance in  
 real-time via smartphone app or  
 web portal using our advanced  
 monitoring platform.



For more about the Fox ESS range of inverters, visit:

[www.fox-ess.com](http://www.fox-ess.com)



# TECHNICAL SPECIFICATIONS

MODEL	M1-600	M1-800	M1-1000	M1-1200
<b>INPUT (PV)</b>				
Applicable module power [W]	355Wp-670Wp+			
Peak power tracking voltage [V]	31 ~ 45			
Max. Input Voltage [V]	60			
Start-up voltage [V]	24			
Max. Input Current [A]	20			
Max. Input Short-circuit Current [A]	24			
Number of MPPTs	2			
Number of Strings per MPPT	1			
DC over-voltage protection class	II			
<b>OUTPUT (AC)</b>				
Nominal output power [W]	600	800	1000	1200
Nominal output apparent power [VA]	600	800	1000	1200
Peak output apparent power [VA]	600	800	1000	1200
Nominal output current [A]	2.72	3.64	4.54	5.46
Nominal output voltage/range [V] <sup>*1</sup>	230/180 ~ 264			
Nominal output frequency [Hz] <sup>*1</sup>	50/45 ~ 55 or 60/55 ~ 65			
Power Factor	>0.99( Adjustable from 0.8 leading to 0.8 lagging )			
Max. Total Harmonic Distortion [%]	< 3			
Max. units per 10AWG branch <sup>*2</sup>	11	8	7	5
Max. units per 12AWG branch <sup>*2</sup>	9	6	5	4
AC over-voltage protection class	III			
<b>EFFICIENCY</b>				
EU Weighted Efficiency [%]	95.50			
CEC Weighted Efficiency [%]	95.50			
Max. Efficiency [%]	96.00			
Nominal MPPT Efficiency [%]	99.90			
<b>GENERAL DATA</b>				
Dimensions (WxHxD) [mm]	270*182*34.5			
Weight [kg]	3.9			
Cooling Method	Natural convection-No fans			
Ingress Protection(according to IEC60529)	IP67			
Max. Operating Altitude [m]	2000			
Operating Ambient Temperature Range [°C]	-25 ~ +65			
Allowable Relative Humidity Range [%]	1 ~ 100			
Nominal nighttime consumption [mW]	< 50			
Communication	WIFI			
Isolation type	Reinforce Isolation			
Monitoring <sup>*3</sup>	Fox ESS Cloud			
<b>STANDARD</b>				
Safety	IEC62109-1/2			
EMC	IEC 61000-6-1 /IEC 61000-6-2 /IEC 61000-6-3 /IEC 61000-6-4 /IEC61000-3-2/IEC61000-3-3			
Certification	ABNT NBR 16150, EN 50549-1: 2019, VDE-AR-N 4105: 2018, VFR2019			

\*1 Nominal voltage/frequency range can vary depending on local requirements.

\*2 Refer to local requirements for exact number of microinverters per branch.

\*3 Fox ESS Monitoring System.